


Economical, Compact Material Mixing

Model FS2, shown at right, and Model FS3 feature angle iron construction. Model FS1 has a solid sheet metal top surface with an opening for the adapter plate.

When ordering, please detail the equipment to be mounted on the stand so that the correct adapter plate may be specified.



A 1/4 inch thick adapter plate, matching the bolt pattern of the auxiliary equipment, is bolted to the top of the floor stand.

- ▶ **Standard and custom sizes**
Ensure the perfect fit for your equipment
- ▶ **Mounting pads on legs**
Allow stand to be bolted to the floor
- ▶ **Full welded construction**
Provides strength and durability
- ▶ **Optional casters***
Make movement easy

Specifications

Models	Standard Models			Custom Models		
	FS1	FS2	FS3	FS1	FS2	FS3
Maximum weight capacity lb {kg}	1000 {454}	2000 {907}	3000 {1361}	1000 {454}	2000 {907}	3000 {1361}
Outside dimensions inches {mm}						
Height	29 {737}	66 {1676}		12-42 {305-1067}	18-66 {457-1676}	
Width	30 {762}	60 {1524}		24-36 {610-914}	38-70 {965-1778}	40-70 {1016-1778}
Depth	30 {762}	60 {1524}		24-36 {61-914}	38-70 {965-1778}	40-70 {1016-1778}
Casters*	Casters may be added only if the combined stacked height of the mounted equipment is less than 3.5 times the selected width or depth. If casters are added, specify desired height, less caster dimension (5 inches for FS1, 6 inches for FS2).					
Addition to Height inches {mm}	+5 {127}	+6 {152}	N/A	+5 {127}	+6 {152}	N/A
Inside dimensions inches {mm}	For Custom Models, subtract the value shown from the outside dimensions.					
Height	26.75 {679}	58.25 {1480}	59.25 {1505}	2.25 {57}	7.75 {197}	6.75 {171}
Width	24 {610}	46.5 {1181}	51 {1295}	6 {152}	13.5 {343}	9 {229}
Depth	25 {635}	51.25 {1302}	51 {1295}	5 {127}	8.75 {222}	9 {229}

Specification Notes

Specifications may change without notice. Consult with a Conair representative for the most current information.

