



3D FILAMENT EXTRUSION LINE - HIGH SPEED LINE

Designed to produce high quality, close tolerance, void free 3D printer filament

Products: 1.7mm diameter (+/-.001 in.)

ABS & PLA materials (other available)

400 to 600 ft./min.

dX50 Mobile Dryer

with wheel drying technology



- 6 cu.ft. hopper including loading for drying hopper and extruder
- · PLC control with color touchscreen

2 in. Extruder (24:1)

with microprocessor touch screen control, drive & screw



 All components are premounted and prewired

Tooling Package

for two product diameters



- Rod die
- Tank preskinner
- Including extruder die adapter & heaters

HTMP-18-4 Vacuum Sizing Tank

with water air separation for accurate stable vacuum



- · 3 plane adjustment for easy alignment
- Vacuum & recirculation systems with heating
- PAVC+ touchscreen control
- Servo wheel drive
- · Split design air wipe

Diameter Measuring System

with feedback loop to the vacuum tank to maintain the product diameter



- Tri plane laser with mounting at the entrance to the puller
- Touchscreen controls mounted at the tank for easy operator access

EP1A-03 Portable Chiller



- · 3 Ton Air-cooled
- · Auto water makeup with controls

4-26 Belt Puller

precision puller for better product control



- · 4 in. x 26 in. traction belts
- · Product guides
- Touchscreen HMI
- Full belt safety enclosure
- · Servo drive

ATC-24

automatic tubing coiler



- Touchscreen HMI
- · Dual reels with traverse
- · Ultrasonic bobbin loop control
- Servo spool drives, turret & traverse

Project Engineering, System Testing at the Conair Technical Center to ensure all components are producing acceptable product prior to shipment as well as the preliminary customer training followed by startup at the customer facility with additional training.

Price: \$528,235

Lead Time: TBA

Terms & Conditions: To be advised

3D FILAMENT EXTRUSION LINE - LOW SPEED LINE

Designed to produce high quality, close tolerance, void free 3D printer filament

Products: 1.7mm diameter (+/-.001 in.)

ABS & PLA materials (other available)

200 ft./min.

dX50 Mobile Dryer

with wheel drying technology



- 6 cu.ft. hopper including loading for drying hopper and extruder
- · PLC control with color touchscreen

1.5 in. Extruder (24:1)

with microprocessor touch screen control, drive & screw



 All components are premounted and prewired

Tooling Package

for two product diameters



- Rod die
- Tank preskinner
- Including extruder die adapter & heaters

MT 104-16-4 Vacuum Sizing Tank

with water air separation for accurate stable vacuum



- · 3 plane adjustment for easy alignment
- Vacuum & recirculation systems with heating
- · PAVC+ touchscreen control
- Split design air wipe

Diameter Measuring System

with feedback loop to the vacuum tank to maintain the product diameter



- Tri plane laser with mounting at the entrance to the puller
- Touchscreen controls mounted at the tank for easy operator access

EP1A-03 Portable Chiller



- · 3 Ton Air-cooled
- · Auto water makeup with controls

3-20 Belt Puller

precision puller for better product control



- · 3 in. x 20 in. traction belts
- · Product guides
- Touchscreen HMI
- Full belt safety enclosure
- · Servo drive

MTC-24

manual tubing coiler



- · Dual reels with traverse
- · Ultrasonic bobbin loop control
- AC spool drives and mechanical traverse

Project Engineering, System Testing at the Conair Technical Center to ensure all components are producing acceptable product prior to shipment as well as the preliminary customer training followed by startup at the customer facility with additional training.

Price: \$346,412

Lead Time: TBA

Terms & Conditions: To be advised



Conair Corporate Office and Technology Center

200 West Kensinger Dr. Cranberry Township, PA 16066 724-584-5000 info@conairgroup.com www.conairgroup.com

Extrusion Technology Center

503 S. Mercer St. Pinconning, MI 48650 989-684-6877 info@conairgroup.com www.conairgroup.com